



US006626305B2

(12) **United States Patent**
Domenig et al.

(10) **Patent No.:** US 6,626,305 B2
(45) **Date of Patent:** *Sep. 30, 2003

(54) **ROTARY SHELF ASSEMBLY MECHANISM HAVING A POST HEIGHT ADJUSTMENT DEVICE AND A NOVEL SHELF CONSTRUCTION AND SHELF RETAINING ELEMENT FOR SECURING THE SHELVES TO THE POST**

(76) Inventors: **Georg Domenig**, 1110 Whispering Pines, Kernersville, NC (US) 27284; **James Rapier**, 109 Shamrock Dr., Salisbury, NC (US) 28144

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: 09/740,554

(22) Filed: Dec. 20, 2000

(65) Prior Publication Data

US 2002/0074471 A1 Jun. 20, 2002

Related U.S. Application Data

(63) Continuation-in-part of application No. 09/640,052, filed on Aug. 17, 2000, now abandoned.

(51) Int. Cl.⁷ A47F 5/02

(52) U.S. Cl. 211/144; 211/95; 211/163; 211/131.1; 211/129.1

(58) Field of Search 211/95, 163, 207, 211/208, 131.1, 129.1, 78, 144; 403/109.1, 109.2, 109.4, 379.3, 378; 312/305; 248/250

(56) References Cited

U.S. PATENT DOCUMENTS

918,579 A	*	4/1909	Murch	248/353
2,124,842 A	*	7/1938	Zierold et al.	135/26
2,350,582 A	*	6/1944	Booth	403/379.3
2,423,577 A	*	7/1947	Booth	403/379.3

3,628,844 A	*	12/1971	Preston	312/305
4,433,885 A		2/1984	Baker		
4,486,106 A	*	12/1984	Benting	384/248
4,572,595 A		2/1986	Craig		
4,587,908 A		5/1986	DeBruyn		
4,616,940 A		10/1986	DeBruyn		
4,688,686 A	*	8/1987	Mitts et al.	211/183
4,819,900 A	*	4/1989	Funk	248/244
5,050,746 A	*	9/1991	Frankel	211/34
5,287,869 A	*	2/1994	Wu	135/25.1
5,312,003 A		5/1994	Domenig		
5,354,025 A	*	10/1994	McCaffrey	248/188
5,494,346 A		2/1996	Domenig		
5,702,198 A	*	12/1997	Kuo	403/377
5,931,315 A	*	8/1999	Lorentz et al.	211/40
5,941,399 A	*	8/1999	Wang	211/187
6,017,108 A		1/2000	Domenig		

* cited by examiner

Primary Examiner—Gregory J. Strimbu

ABSTRACT

A rotary shelf assembly mechanism has shelves mounted on a vertical post arrangement formed by a first lower post and a second upper post. The mechanism is connected to a cabinet by upper and lower mounting brackets interacting with the top and bottom of the cabinet to support the posts and shelves carried thereby. The mechanism is mounted in the corner of the cabinet. To fit the mechanism within the cabinet, a height adjustment device is formed by positioning the second upper post in the upper end of the first lower post for slidable movement therebetween. When securement of the two joined posts and mounted shelves is desired, the slidably movable second upper post is extended upwardly until it engages the upper mounting bracket mounted on the cabinet. An elongated recess in the second upper post aligns with an opening in the first lower post, and a threaded member extends into a casting positioned within the upper post. The threaded member is tightened to engage the casting and secure the two posts in a shelf-retaining and rotational mode. The height adjustment device enables quick and efficient installation of the mechanism within the cabinet interior. The mechanism also includes a one piece shelf construction having a post-securing section and a shelf-retaining pin.

4 Claims, 10 Drawing Sheets

